


Poured concrete spacer with eyelet wire



The GB ÖD cast concrete shoring with eyelet wire can be used with horizontal and vertical reinforcement. The large contact area makes the GB ÖD very stable and highly resilient. The Bipo is manufactured with a round, flat contact surface. The inserted eyelet wire is galvanized.

| Article number | Title of variant | Concrete cover mm | a mm | Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can | Packaging piece/pallet | Weight kg/100 pieces |
|----------------|---|-------------------|------|---|------------------------|----------------------|
| 23170000 | GB 20 ÖD cast concrete support with eyelet wire | 20 | 40 | 240 pieces/bag | 8640 | 5,800 |
| 23171000 | GB 25 ÖD poured concrete support with eyelet wire | 25 | 40 | 240 pieces/bag | 8640 | 7,200 |
| 23172000 | GB 30 ÖD poured concrete support with eyelet wire | 30 | 40 | 240 pieces/bag | 8640 | 8,870 |
| 23173000 | GB 35 ÖD poured concrete support with eyelet wire | 35 | 40 | 160 pieces/bag | 5760 | 10,300 |
| 23174000 | GB 40 ÖD cast concrete support with eyelet wire | 40 | 40 | 160 pieces/bag | 5760 | 12 |
| 23175000 | GB 45 ÖD poured concrete support with eyelet wire | 45 | 40 | 160 pieces/bag | 5760 | 13,560 |
| 23176000 | GB 50 ÖD poured concrete support with eyelet wire | 50 | 40 | 160 pieces/bag | 4800 | 15,590 |
| 23177000 | GB 60 ÖD cast concrete support with eyelet wire | 60 | 40 | 128 pieces/bag | 3840 | 18,620 |