


## Roka-Q acid-resistant



Roka-Q with transverse groove is mounted on the horizontal reinforcing steel. The two spring steel clamps  $\varnothing$  2 mm are placed over the vertical reinforcing steel and clamp the Roka optimally to the reinforcing steel. Quick installation is guaranteed. The bevel is used to guide the reinforcement cage into the formwork. This prevents the formwork from catching on the spacer. The groove width and depth are produced as required.



Article number	Title of variant	Length mm	Concrete cover mm	Weight kg/100 pieces	Packaging piece/gibo
22242400	Roka-Q with cross groove 25 acid-resistant	30	25	7,900	8.000
22243400	Roka-Q with cross groove 30 acid-resistant	30	30	9	7.000
22244400	Roka-Q with cross groove 35 acid-resistant	30	35	11,500	6.000
22245400	Roka-Q with cross groove 40 acid-resistant	30	40	14	5.000
22246400	Roka-Q with cross groove 45 acid-resistant	30	45	18,900	4.500
22247700	Roka-Q with cross groove 50 acid-resistant	30	50	23,100	4.000
22248400	Roka-Q with cross groove 60 acid-resistant	30	60	27	3.500
22249400	Roka-Q with cross groove 70 acid-resistant	30	70	30,900	3.000