


GripTec GTB positioning joint II



Positioning coupling GripTec GTB-P II for straight and bent, not free-rotating and / or longitudinally fixed rebars (PII).

Technical data

Minimum distance according DIN 1045-1 1 ds / min. 2 cm

* Thread pitch does not correspond to standard pitch.

| Article number | Thread | Ø mm | BSt Ø mm | a mm | b mm | L mm | ±L mm | SW mm | Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can | Weight kg/piece |
|----------------|-----------|------|----------|------|------|------|-------|-------|---|-----------------|
| 32121440 | M 14x2,0 | 20 | 12 | 70 | | 153 | 35 | 22 | 1 piece | 0,320 |
| 32141640 | M 16x2,0 | 24 | 14 | 85 | | 172 | 33 | 24 | 1 piece | 0,360 |
| 32161840 | M 18x2,5 | 26 | 16 | 100 | | 197 | 36 | 27 | 1 piece | 0,620 |
| 32202240 | M 22x2,5 | 34 | 20 | 115 | | 225 | 37 | 32 | 1 piece | 1,090 |
| 32252740 | M 27x3,0 | 40 | 25 | 120 | | 249 | 45 | 41 | 1 piece | 1,840 |
| 32283040 | M 30x2,5* | 45 | 28 | 105 | | 241 | 47 | 46 | 1 piece | 2,520 |
| 32323340 | M 33x3,5 | 50 | 32 | 140 | 101 | 287 | 45 | 50 | 1 piece | 3,390 |
| 32404240 | M 42x4,5 | 65 | 40 | 170 | 117 | 289 | 49 | 65 | 1 piece | 6,740 |